



PCT/GB 2003 / 0 0 4 0 1 3

Rec'd PCT/PTO 1 MAR 2005

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

10/528206

REC'D 23 OCT 2003

WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed *Andrew Gersy*
Dated 6 October 2003


**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

BTECH001-UK

2. Patent application number

(The Patent Office will fill in this part)

0221624.0

18 SEP 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

B-TECH INTERNATIONAL LIMITED
Vulcan House
Vulcan Way
New Addington
Croydon CR0 9UG
UK

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

8467 11 0001

4. Title of the invention

Loudspeaker Wall Bracket

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Lucas and Co.
135 Westhall Road
Warlingham
Surrey
CR6 9HJ
05815709001 ✓

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

| | |
|-------------|---|
| Description | 5 |
| Claim(s) | 3 |
| Abstract | 1 |
| Drawing(s) | 2 |

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

| | |
|--|---|
| Statement of inventorship and right to grant of a patent (Patents Form 7/77) | 1 |
|--|---|

| | |
|--|---|
| Request for preliminary examination and search (Patents Form 9/77) | 1 |
|--|---|

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

16 Sep 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Tony Miller - 01883 626211

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

LOUDSPEAKER WALL BRACKET

5 The present invention relates to wall brackets for loudspeakers and the like.

Wall brackets are well known for loudspeakers and typically comprise a plate for attachment to the wall and a ball and a socket arrangement for mounting the loudspeaker, whereby the latter can be pointed in a desired direction.

10

According to the present invention a wall bracket for a loudspeaker or the like comprises:

a wall plate arranged for attachment to a wall, the plate having at least a pair of raised, laterally projecting flanges;

15 a bracket base arranged for engaging with the flanges and being thereby held to the wall plate; and

a bracket mount arranged for attachment to a loudspeaker or the like; there being a ball and socket arrangement between the bracket base and the bracket mount whereby the bracket mount may be locked to the bracket base

20 in a variety of configurations.

The invention provides a number of advantages over known such wall brackets. One is aesthetic, in that screws or the like holding the bracket to the wall need not be visible. Another is that neither the bracket configuration
25 nor the wall plate have to be disturbed when the loudspeaker etc is removed from the wall.

For aesthetic and simplicity considerations it is preferred that the flanges project outwards of the wall plate rather than inwards. In a preferred
30 embodiment of the invention the engagement of the bracket base with the projecting flanges is accomplished by sliding the bracket base onto the flanges, which may be in parallel or convergent array. However the bracket base may be arranged to clip over one of the flanges and a grub screw in the

bracket base, preferably at the top thereof, used to engage behind an opposing flange.

5 Another advantage conferred by the projecting flange means of attachment is in readily permitting the use of a substantially two part bracket base. Each of the two parts of the bracket base may include a socket forming part of the said ball and socket arrangement. By this means the ball may be interposed between two substantially hemispherical sockets, and held therebetween in a vice-like manner. Preferably the two parts of the bracket base have
10 interfitting members, for example pegs and associated holes whereby the two parts of the bracket base can be manually held together, with the ball in place, while the wall bracket is assembled. This assembly can then be mounted on the wall plate. A grub screw may be fitted in the bracket base to lock it to the wall plate.

15 Ideally the ball is pierced in the longitudinal direction, as are the sockets, and the bracket is clamped together by a bolt passing through the two sockets and the ball. The arrangement is preferably such as still to permit the ball to be held so that the loudspeaker etc may have a variety of inclinations with respect to the wall bracket. For example the hole through the ball may be
20 enlarged, at least towards the surface of the ball. The bolt fixing may be an external nut or one nestling within or moulded within one of the two parts of the bracket base. The bolt may have an enlarged head to enable it to be finger tightened. On the other hand the bolt head may interfit a bracket base
25 part or be moulded therewith and the nut may be large enough for finger tightening.

30 The bracket mount may have a concave mounting surface and will usually incorporate holes or slots for attachment of the loudspeaker etc. Ideally the bracket mount has a mounting surface, which comprises two saddles, on a normal to the other, in this way the mount may be aesthetically adapted for attachment to loudspeakers with curved or flat rear or side surfaces. An adapter or suite of adapters may be provided for enabling loudspeakers etc

of differing sizes and mounting provisions to be attached to the wall bracket.

5 It is also convenient if the wall plate has a cable management hole whereby cabling for the loudspeaker etc can be routed therethrough and possibly between the two parts of the bracket base, thereby concealing the emergence thereof from the wall and indeed minimizing cable visibility generally.

10 The invention has been primarily conceived for use with relatively small (maximum dimensions about 20cm x 15cm x 10cm) loudspeakers of the sort used in the home theatre or home cinema context. However the expressions "and the like" and "etc" in this patent specification are intended to provide cover for use of a wall bracket in accordance with the invention with such
15 other electrical/electronic items of equipment as movement detectors, cameras and video recorders and projectors, security and wall lights, and even personal computer monitors and televisions.

A particular embodiment of the present invention will now be described by way of example with reference to the accompanying drawings, of which:-

20

Figure 1 is an exploded view of a wall bracket in accordance with the invention, and

Figure 2 is an isometric view of an assembled wall bracket.

25

The wall bracket shown in the drawings comprises a wall plate 20, a lower bracket base member 30, an upper bracket base member 40, a bracket mount member 50, a bolt 60 and an adapter 70.

30 The wall plate 20 is a metal plate with two raised flanges 21a, 21b projecting laterally outwards, wall fixing holes 22, a centrally disposed cable management hole 23, and a grub screw threaded anchor hole 24.

The lower bracket base member 30 comprises a housing 31 incorporating grooves 32 arranged for engagement with the wall plate flanges 21a, 21b, and a jaw member 33. The jaw member 33 is integral with the housing 31 and has a substantially hemispherical socket 34 with a central hole 35 therethrough for the bolt 60. This hole 35 holds a nut (not shewn) for the bolt 60. The jaw member 33 faces longitudinally of the member 30. Pins 36 in the housing are arranged to engage in holes (not shewn) in the lower bracket base member 40.

The upper bracket base member 40 comprises a housing 41 incorporating grooves (not shewn) similar to those 32 in the member 30, and a jaw member 42 integral with the housing 41. The jaw member includes a substantially hemispherical socket matching the socket 34 and which in use will oppose and co-operate with the socket 34. There is a central hole 43 through the socket for the bolt 60. There is a grub screw (47) centrally in the upper face of the housing 41, for engaging with the anchor hole 24 in the wall plate 20. The housing 41 extends a short way upward of the jaw member 42, to allow the cabling to be routed therethrough.

The bracket mount member 50 comprises a mounting ball 51 and a bracket 52 integral with the ball 51. The ball 51 is of similar radius to the sockets in the base members 30 and 40 and is arranged for being captured and gripped therebetween. The ball 51 has a slot 53 therethrough for the bolt 60. The slot 53 permits the member 50 to be held in a variety of configurations with respect to the members 30, 40. The bracket 52 is formed with two saddles 52a, 52b normal one to the other, and a central hole 54 for the attachment of a loudspeaker (not shewn).

The adapter 70 is a plate with a central hole 71 for attachment thereof to the bracket 52 at the hole 54 and two outlying holes 72 for attachment to a loudspeaker or the like.

For using the wall bracket shewn in the drawings the wall plate 20 is attached

- 5 -

to a wall in a desired location and cabling, terminating in a plug/socket, is brought through the central hole 23. The loudspeaker is offered to and attached to the bracket 52 via the hole 54. The lower bracket member 30 is slid onto the grooves 21a, 21b of the wall plate 20 and while held in position, perhaps via the grub screw, the ball 51, nestling in the socket of the lower bracket base member 40, is offered to the lower socket 34, the lower base member 30 being slid onto the grooves 21a, 21b. The bolt 60 is then passed through the jaws and the ball 51 and tightened with the loudspeaker held in the desired configuration. The electrical connection is then made.

10

The above described modus operandi is particularly suitable for small loudspeakers having a rounded back. Flat backed loudspeakers can be attached to the wall bracket using the adapter 70.

CLAIMS

1. A wall bracket for a loudspeaker or the like and comprising:
a wall plate arranged for attachment to a wall, the plate having at least a pair
5 of raised flanges;
a bracket base arranged for engaging with the flanges and being thereby
held to the wall plate; and
a bracket mount arranged for attachment to a loudspeaker or the like;
there being a ball and socket arrangement between the bracket base and the
10 bracket mount whereby the bracket mount may be locked to the bracket base
in a variety of configurations.
2. A wall bracket as claimed in claim 1 and wherein the flanges project
laterally of the wall plate.
15
3. A wall bracket as claimed in claim 2 and wherein the flanges project
laterally outwards.
4. A wall bracket as claimed in any one of the preceding claims and
20 wherein the bracket base is arranged for sliding over the flanges thereby to
be held to the wall.
5. A wall bracket as claimed in any one of the preceding claims and
wherein the flanges are in parallel array.
25
6. A wall bracket as claimed in claim 1 and wherein the bracket base is
arranged to clip over one of the flanges and a grub screw in the bracket base
used to engage behind an opposing flange.
- 30 7. A wall bracket as claimed in any one of the preceding claims and
wherein the bracket base is substantially in two parts.
8. A wall bracket as claimed in claim 7 and wherein each of the two

parts of the bracket base includes a socket forming part of the said ball and socket arrangement, whereby the ball may be interposed between two substantially hemispherical sockets, and held therebetween in a vice-like manner.

5

9. A wall bracket as claimed in claim 7 or claim 8 and wherein the two parts of the bracket base have interfitting members whereby the two parts of the bracket base can be manually held together, with the ball in place, while the wall bracket is assembled.

10

10. A wall bracket as claimed in any one of the preceding claims and arranged such as to permit the ball to be held so that the loudspeaker etc may have a variety of inclinations with respect to the wall bracket.

15

11. A wall bracket as claimed in any one of the preceding claims and wherein the ball is pierced in the longitudinal direction, as are the sockets, and the bracket is clamped together by a bolt passing through the two sockets and the ball.

20

12. A wall bracket as claimed in claim 11 and wherein the hole through the ball is enlarged, at least towards the surface thereof of the ball whereby the loudspeaker or the like may be held in a variety of configurations with respect to the wall.

25

13. A wall bracket as claimed in claim 11 or claim 12 and wherein the bolt has an enlarged head to enable it to be finger tightened.

30

14. A wall bracket as claimed in any one of the preceding claims and wherein the bracket mount has a concave mounting surface, whereby it is adapted for holding loudspeakers with curved or flat rear or side surfaces.

15. A wall bracket as claimed in any one of the preceding claims and wherein the bracket mount has two mounting saddles, one normal to the

other, where? it is adapted to carry loudspeakers with curved or flat rear or side surfaces.

5 16. A wall bracket as claimed in any one of the preceding claims and wherein the bracket mount incorporates holes or slots for attachment of the loudspeaker etc.

10 17. A wall bracket as claimed in any one of the preceding claims and wherein the wall plate has a cable management hole whereby cabling for the loudspeaker etc can be routed therethrough.

18. A wall bracket as claimed in any one of the preceding claims and adapted for use in a domestic context.


15 19. Use of a wall bracket according to any one of the preceding claims in a home theatre or home cinema context.

20 20. A wall bracket substantially as hereinbefore described with reference to the accompanying drawings.

ABSTRACT

5 A wall bracket for a loudspeaker or the like, particularly for use in the home
theatre context, and comprising a wall plate (20) arranged for attachment to a
wall, the plate having at least a pair of raised, laterally outward projecting
flanges (21a, 21b); a bracket base arranged for engaging with the flanges
and being thereby held to the wall plate, the bracket base having two
substantially similar opposing parts (30, 40) each incorporating a
substantially hemispherical socket (34); and a bracket mount (50) arranged
10 for attachment to the loudspeaker etc, the bracket mount incorporating a ball
member (51) adapted to be gripped between the bracket base sockets in a
variety of configurations.

15






Fig 1




Fig 2